

NAVAL INVENTORY CONTROL POINT				CODE IDENT		SPI NUMBER	
SPECIAL PACKAGING INSTRUCTION (SPI)				03950		10139	
NOMENCLATURE BLANKET, TYPE 6				NATIONAL STOCK NO. 7H 5840-01-437-9525		SPI DATE 29 Oct 1996	
						REV	
QUP	MAXIMUM UNIT PACKAGE WEIGHT	MAXIMUM UNIT PACKAGE CUBE	MAXIMUM UNIT PACKAGE DIMENTIONS			DRAWN BY : KWS APPROVED : <i>[Signature]</i>	
001	14.0 lbs	1.341 cu ft	8" X 8" X 36.2"			SHEET 1 OF 2	

PRESERVATION, PACKAGING and PACKING REQUIREMENTS PER MIL-STD-2073:

H	M	QUP	ICQ	PRES METH	C D	PRES MATL	WRAP MATL	CUSH DUNN	C T	UNIT CTNR	L P	INTM CTNR	U C	SPEC MKG	PACK ING	UNIT PACK WGHT	UNIT PACK CUBE	O P I
N		001	025	10	1	00	CA	00	0	ED	A	DP	A	51	FFF	14.0	1.349	A

1. The item shall be packaged in accordance with the above packaging requirements code and the following:

a. Each panel shall be rolled, with "D" rings toward center, on a 4" diameter core. Wrap, each rolled panel, with 36" wide brown kraft paper tape in three places then remove the core. Affix a label to the kraft paper denoting the product name and serial number.

b. Each rolled item shall be inserted into a fiberboard box with an identical label affixed to the outside of the box. The box shall be marked with the following:

"WARNING - DO NOT LAY FLAT"

Rolls shall be maintained in a vertical position at all times to prevent creasing during handling, shipping and storage.

c. Up to 25 of these boxed units, with sequential serial numbers, shall be inserted on end in a TRI-WALL fiberboard container (see FIGURE A on page two) which is placed on a pallet. Packing lists shall be enclosed in an envelope at the top, lids shall be folded over, stapled and taped closed. A shipping label shall be affixed to the TRI-WALL container denoting the serial numbers of the panels within.

NAVAL INVENTORY CONTROL POINT		CODE IDENT	SPI NUMBER
SPECIAL PACKAGING INSTRUCTION (SPI)		03950	10139
NOMENCLATURE BLANKET, TYPE 6	NATIONAL STOCK NO. 7H 5840-01-437-9525	SPI DATE 29 Oct 1996	REV

SHEET 2 OF 2

FIGURE A

